

Safety Data Sheet Lemon Fusion

1. IDENTIFICATION

Synonyms none

CAS# see Part 3, below
Material Use carpet deodorizer

IN AN EMERGENCY CALL: INFOTRAC 1-800-535-5053

2. HAZARD IDENTIFICATION

GHS Class	skin irritant	eye irritant	combustible	
(Category)	(3)	(2A)	<i>(4)</i>	
Signal Words	WARNING	WARNING	WARNING	
	no Pictogram		no Pictogram	
Hazard Statements	causes mild	causes serious	combustible	
	skin irritation	eye irritation	liquid	
	(H315)	(H319)	(H227)	



GHS Precautionary Statements for Labeling

P210, P370	Keep away from hot surfaces. In case of fire, use water spray to extinguish.
P262, P264	Do not get in eyes, on skin or on clothing. Wash thoroughly after handling.
P270, P280	Do not eat, drink or smoke when using this product. Wear protective gloves of rubber.
P273	Avoid release to the environment.

3.	COMPOSITION	CAS NUMBER	%	TLV ppm / mg/m³	LD ₅₀ (mg/kg) ORAL	LD ₅₀ (mg/kg) SKIN	LC ₅₀ ppm INHALATION
2-Propanol		67-63-0	1-10%	200 / 490	>4400	12,900	>5920ppm
Nonionic Surfactant		on request	1-10%	not listed	>2000	not known	not known
Proprietary Lemon so	cent	not known	1-5%	not listed	4500	4150	not known
Water		7732-18-5	balance	not toxic	90.000	not toxic	not toxic

NOTE: Several other substances are present at below 0.5%; none are sufficiently hazardous to require listing at above 0.1%.

4. FIRST AID

SKIN: Wash with plenty of water. Remove contaminated clothing and do not reuse until laundered. Seek medical help

promptly if there is persistent itching or redness in the affected area.

EYES: Wash eyes with plenty of water, holding eyelids open. Seek medical assistance if there is any irritation. INHALATION: Remove from contaminated area promptly. **CAUTION: Rescuer must not endanger himself!** If victim's

breathing stops, administer artificial respiration and seek medical aid promptly.

INGESTION: Give plenty of water to dilute product. Do not induce vomiting (NOTE below). Keep victim quiet. If vomiting

occurs, lower victim's head below hips to prevent inhalation of vomited material. Seek medical help promptly.

NOTE: Inadvertent inhalation of vomited material may seriously damage the lungs. The danger of this is greater than the risk of poisoning through absorption of this low-toxicity product. The stomach should only be emptied under medical supervision, after the installation of an airway to protect the lungs.

cont'd next page

PLEASE ENSURE THAT THIS SDS IS GIVEN TO, AND EXPLAINED TO PEOPLE USING THIS PRODUCT.

EMERGENCY INFORMATION: INFOTRAC 1-800-535-5053

5. FLAMMABILITY & FIRE-FIGHTING

Flash Point not measured; above 60°C / 140°F

Autoignition Temperature not known – may burn under fire conditions

Flammable Limits not known

Combustion Products carbon monoxide, nitrogen oxides, smoke, part oxidized hydrocarbon fragments

Firefighting Precautions as for materials sustaining fire; firefighters must wear SCBA

Static Discharge cannot accumulate a static charge

6. ACCIDENTAL RELEASE MEASURES

Leak Precaution dike to control spillage and prevent environmental contamination

Handling Spill recover free liquid with suitable pumps; absorb residue on an inert sorbent, sweep, shovel & store in closed

containers for disposal

7. HANDLING & STORAGE

Store and use in a cool dry environment, away from open flames and oxidizing agents. Always replace cap prior to moving the container!

Avoid generating or breathing product vapor or mist. If mist or vapor form in use, install adequate ventilation to maintain airborne concentration of the product below the TLV (*see Part 8, below*). Avoid prolonged contact with skin and wash work clothes frequently. An eye bath should be available near the workplace.

8. EXPOSURE CONTROL & PERSONAL PROTECTION

2-Propanol:

 $\begin{array}{lll} ACGIH\ TLV & 200ppm\ /\ 491mg/m^3 & ACGIH\ STEL\ 400ppm\ /\ 983mg/m^3 \\ OSHA\ PEL & 400ppm\ /\ 980mg/m^3 & OSHA\ STEL\ 500ppm\ /\ 1225mg/m^3 \\ \end{array}$

Ventilation no special mechanical ventilation required

Hands wear rubber gloves – other types also protect; always confirm suitability with supplier

Eyes safety glasses with side shields – *always protect eyes!*

Clothing no special protective clothing required

9. PHYSICAL AND CHEMICAL PROPERTIES

Odor & Appearance clear, slightly yellow liquid with an odor of lemon

Odor Threshold not known

Vapor Pressure below 33mmHg / 4.4kPa (20°C/ 68°F) – isopropanol

Evaporation Rate (Butyl Acetate = 1) as for water

Vapor Density (air = 1) 0.6 (water), 2.1 (isopropanol); other components do not form a vapor

Boiling Point approx. 100°C / 212°F
Freezing Point approx. -5°C / 23°F
Specific Gravity 0.982-0.996 (20/20°C)

Water Solubility complete
Viscosity not known
pH 6.5-8.5

cont'd next page

10. REACTIVITY

Dangerously Reactive With none known Also Reactive With none known

Chemical Stability stable; will not polymerize
Decomposes in Presence of
Decomposition Products as for Combustion Products, above

Mechanical Impact not sensitive

11. TOXICITY INFORMATION

i. ACUTE EXPOSURE

Skin Contact may irritate skin if exposure is prolonged – through removal of natural skin oils

Skin Absorption slight; toxic effects unlikely by this route

Eye Contact severely irritating Inhalation no effects known

Ingestion headache, dizziness, drowsiness, intoxication, vomiting & stomach ache

Calculated LD_{50} (oral) 16,270mg/kg (rat) Calculated LD_{50} (skin) 87,330mg/kg (rabbit)

LC₅₀ (inhalation) insufficient information to calculate

ii. CHRONIC EXPOSURE

General prolonged or repeated exposure may cause dermatitis

Sensitizing the (proprietary) scent is considered a sensitizer if applied to the skin as part of a cosmetic product;

in view of this warning, it is prudent to limit skin contact as much as possible

Carcinogen/Tumorigen not known to be a tumorigen or a carcinogen in humans or animals

Reproductive Effect no known effect on humans or animals

Mutagen not known to be a mutagen or teratogen in humans or animals

Synergistic With not known

12. ECOLOGICAL INFORMATION

2-Propanol:

Bioaccumulation low potential for bioaccumulation

Biodegradation biodegrades readily & rapidly; aerobic >75% in 28 days; anaerobic >65% in 20 days Abiotic Degradation reacts with atmospheric hydroxyl (OH) radicals; estimated ½-life in air 3.2 days

Mobility in soil, water water soluble; moves readily through soil and the water column

Aquatic Toxicity

LC₅₀ (Fish, 96) 9640, 10,400 & 11,130mg/liter (Pimephelas promelas), 4200mg/liter (Rasbora heteromorpha)

LC₅₀ (Crustacea, 48) 1100 & 1400mg/l (Crangon crangon), 13,300mg/liter (Daphnia magna)

EC₅₀ (Algae, 96hr) 1000mg/l (Scenedesmus subspicatus)

LC₅₀ (Microorganisms) 1050 & 5175mg/l (Pseudomonas putida), 41,676mg/liter ("activated sludge, domestic sewage")

Nonionic Surfactant:

Bioaccumulation surfactant does not bioaccumulate; the breakdown product, unethoxylated nonylphenol, does accumulate,

and is toxic to aquatic life

Biodegradation biodegrades readily in the presence of oxygen; 34% biodegradation in 20 days yielding di- & mono-ethoxylate;

these latter compounds resist further biodegradation

Abiotic Degradation not known

Mobility in soil, water sufficiently water soluble to move readily through soil and the water column

Aquatic Toxicity

LC₅₀ (Fish, 96 hr) 2.1-2.6mg/liter (Pimephelas promelas), 13.9-19.5mg/liter (Poecilia reticulata – 48hr)

LC₅₀ (Crustacea, 48hr) 3.8-6.2 & 18.2mg/liter (Daphnia magna), 20.9mg/liter (Gammarus pulex) EC₅₀ (Algae, 96hr) 15mg/liter (Lemna minor), 7mg/liter (Scenedesmus quadricauda)

cont'd next page

12. ECOLOGICAL INFORMATION, cont'd

Proprietary Lemon Scent:

The manufacturer warns: "Do not allow this material to escape into waters, waste water or soil.", and "Do not allow this material to reach ground water or sewage system."

However, the scent is present as 2.5% of this formulation; too low to warrant a GHS "aquatic toxic" Classification.

No information is given regarding biodegradation, mobility in soil or water, or toxicity to aquatic life.

13. DISPOSAL CONSIDERATIONS

Waste Disposal do not flush to sewer; due to the presence of nonylphenol ethoxylate and the unidentified scent components,

any waste material should be handled by a hazardous waste specialist

Containers **Drums** should be reused. Recondition and pressure test by a licensed reconditioner prior to re-use.

Pails must be vented and thoroughly dried prior to crushing and recycling.

No

IBCs (intermediate bulk containers): polyethylene bottle must be pressure tested & recertified at 30 months. Replace at 60 months (5 years). Steel containers must be inspected, pressure tested & recertified every 5 years.

Warning: never cut, drill, weld or grind on or near this container, even if empty.

14. TRANSPORT INFORMATION

USA 49 CFR & Canada/International TDG

Product Identification Number

Shipping Name

Classification

Marine Pollution

UN – not regulated for transport

not regulated for transport

not regulated for transport

not a marine pollutant

ERAP Required

15. REGULATIONS

Canada DSL on inventory
U.S.A. TSCA on inventory
Europe EINECS on inventory

16. OTHER INFORMATION

Date of Preparation May 2015

Date of Revision -

Prepared for PCS

With data from the Registry of Toxic Effects of Chemical Substances (RTECS), Hazardous Substance Data Base (HSDB), Cheminfo (CCOHS), OSHA, IUCLID Datasheets (European Chemical Substance Information System - ESIS), & others sources (below if used), as required/available

last page of SDS